



(12) **United States Patent**
Samuels et al.

(10) **Patent No.:** **US 8,992,102 B1**
(45) **Date of Patent:** **Mar. 31, 2015**

(54) **CAMERA HOUSING FOR A
SQUARE-PROFILE CAMERA**

USPC 396/12, 25–29, 419, 427, 535; 348/373,
348/374, 376; 455/575.1
See application file for complete search history.

(71) Applicant: **GoPro, Inc.**, San Mateo, CA (US)

(56) **References Cited**

(72) Inventors: **Rudy Lucas Samuels**, Mill Valley, CA
(US); **Christopher Aaron Clearman**,
Half Moon Bay, CA (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **GoPro, Inc.**, San Mateo, CA (US)

8,199,251 B2 * 6/2012 Woodman 348/375
2011/0317065 A1 * 12/2011 Lin et al. 348/373

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

* cited by examiner

Primary Examiner — Clayton E Laballe

Assistant Examiner — Minh Phan

(74) *Attorney, Agent, or Firm* — Fenwick & West LLP

(21) Appl. No.: **14/148,536**

(57) **ABSTRACT**

(22) Filed: **Jan. 6, 2014**


A square camera housing accommodates a square camera
with a substantially square profile. The square camera hous-
ing includes a latching mechanism to secure the camera in the
housing, a mounting mechanism to secure the housing to a
mounting device, and multiple openings in the housing body
to accommodate the camera interface. These features allow
the square camera to be inserted and secured in the square
camera housing in one of a plurality of orientations relative to
the square camera housing.

(51) **Int. Cl.**
G03B 17/00 (2006.01)
G03B 17/02 (2006.01)

(52) **U.S. Cl.**
CPC **G03B 17/02** (2013.01)
USPC **396/419**; 396/535

(58) **Field of Classification Search**
CPC G03B 17/02

17 Claims, 10 Drawing Sheets






FIG. 1a




FIG. 1b




FIG. 1c




FIG. 1d




FIG. 1f




FIG. 1e




FIG. 1g








FIG. 2






FIG. 3e




FIG. 3f




FIG. 3g




FIG. 3h




FIG. 3i




FIG. 3j




FIG. 3m




FIG. 3n




FIG. 3k










FIG. 3l






FIG. 4




FIG. 5b




FIG. 5c




FIG. 5a




FIG. 5e




FIG. 5f




FIG. 5d

1

CAMERA HOUSING FOR A SQUARE-PROFILE CAMERA

BACKGROUND

1. Field of Art

The disclosure generally relates to the field of cameras and in particular to a housing for a square camera.

2. Description of the Related Art

Users, such as sportspersons and outdoor enthusiasts, record high-intensity activities, such as snowboarding, surfing, biking, and stock car racing, with digital cameras. Users capture video and images of these activities on digital cameras secured within camera housings, which protect the camera, hold the camera steady in operation, and allow for hands-free operation of the camera. Furthermore, camera housings protect the camera from physical and environmental damage. Camera housings are typically affixed to another object via camera mounts during use, including bodywear (such as helmets), sporting equipment (such as surfboards), and vehicles (such as motorcycles). However, limited camera housing options make camera housings that can accommodate a wide variety of camera positions and orientations attractive to potential users. Furthermore, a camera housing that can easily secure and release a camera can beneficially improve a user's experience with the camera.

BRIEF DESCRIPTION OF DRAWINGS

The disclosed embodiments have other advantages and features which will be more readily apparent from the detailed description, the appended claims, and the accompanying figures (or drawings). A brief introduction of the figures is below.

FIG. 1*a* illustrates a perspective view of an example square camera, according to one embodiment.

FIG. 1*b* illustrates an alternative perspective view of the square camera, according to one embodiment.

FIG. 1*c* illustrates a rear perspective view of the square camera, according to one embodiment.

FIG. 1*d* illustrates an alternative rear perspective view of the square camera, according to one embodiment.

FIG. 1*e* illustrates a front view of the square camera, according to one embodiment.

FIG. 1*f* illustrates a rear view of the square camera, according to one embodiment.

FIG. 1*g* illustrates a top view of the square camera, according to one embodiment.

FIG. 2 illustrates a block diagram of the square camera's internal electronics, according to one embodiment.

FIG. 3*a* illustrates a perspective view of a narrow-frame square camera housing, according to one embodiment.

FIG. 3*b* illustrates an alternative perspective view of the narrow-frame square camera housing, according to one embodiment.

FIG. 3*c* illustrates a rear perspective view of the narrow-frame square camera housing, according to one embodiment.

FIG. 3*d* illustrates an alternative rear perspective view of the narrow-frame square camera housing, according to one embodiment.

FIG. 3*e* illustrates a front view of the narrow-frame square camera housing, according to one embodiment.

FIG. 3*f* illustrates a rear view of the narrow-frame square camera housing, according to one embodiment.

FIG. 3*g* illustrates a side view of the narrow-frame square camera housing, according to one embodiment.

2

FIG. 3*h* illustrates an alternative side view of the narrow-frame square camera housing, according to one embodiment.

FIG. 3*i* illustrates a bottom view of the narrow-frame square camera housing, according to one embodiment.

FIG. 3*j* illustrates a top view of the narrow-frame square camera housing, according to one embodiment.

FIG. 3*k* illustrates a perspective view of a wide-frame square camera housing, according to one embodiment.

FIG. 3*l* illustrates an alternative perspective view of the wide-frame square camera housing, according to one embodiment.

FIG. 3*m* illustrates a rear perspective view of the wide-frame square camera housing, according to one embodiment.

FIG. 3*n* illustrates an alternative rear perspective view of the wide-frame square camera housing, according to one embodiment.

FIG. 3*o* illustrates a front view of the wide-frame square camera housing, according to one embodiment.

FIG. 3*p* illustrates a rear view of the wide-frame square camera housing, according to one embodiment.

FIG. 3*q* illustrates a side view of the wide-frame square camera housing, according to one embodiment.

FIG. 3*r* illustrates an alternative side view of the wide-frame square camera housing, according to one embodiment.

FIG. 3*s* illustrates a bottom view of the wide-frame square camera housing, according to one embodiment.

FIG. 3*t* illustrates a top view of the wide-frame square camera housing, according to one embodiment.

FIG. 4 illustrates a latching mechanism for a square camera housing, according to one embodiment.

FIG. 5*a* illustrates the insertion of the square camera into the narrow-frame square camera housing, according to one embodiment.

FIG. 5*b* illustrates the camera inserted into the narrow-frame square camera housing in a first configuration, according to one embodiment.

FIG. 5*c* illustrates the camera inserted into the narrow-frame square camera housing in a second configuration, according to one embodiment.

FIG. 5*d* illustrates the insertion of the square camera into the wide-frame square camera housing, according to one embodiment.

FIG. 5*e* illustrates the camera inserted into the wide-frame square camera housing in a first configuration, according to one embodiment.

FIG. 5*f* illustrates the camera inserted into the wide-frame square camera housing in a second configuration, according to one embodiment.

DETAILED DESCRIPTION

The Figures (FIGS.) and the following description relate to preferred embodiments by way of illustration only. It should be noted that from the following discussion, alternative embodiments of the structures and methods disclosed herein will be readily recognized as viable alternatives that may be employed without departing from the principles of what is claimed.

Reference will now be made in detail to several embodiments, examples of which are illustrated in the accompanying figures. It is noted that wherever practicable similar or like reference numbers may be used in the figures and may indicate similar or like functionality. The figures depict embodiments of the disclosed system (or method) for purposes of illustration only. One skilled in the art will readily recognize from the following description that alternative embodiments

3

of the structures and methods illustrated herein may be employed without departing from the principles described herein.

Square Camera System Overview

FIGS. 1a to 1d illustrate perspective views of an example square camera, according to one embodiment. In these figures, the square camera 100 includes a camera lens 102, an interface button 104, and a display 106. As used herein, “square camera” refers to a camera with at least one substantially square cross-section in a two-dimensional plane. The square camera 100, which can be used with the square camera housing, includes a camera exterior that encompasses and protects the camera’s internal electronics, which are further described in FIG. 2. The camera exterior includes 6 surfaces (i.e. a front face, a left face, a right face, a back face, a top face, and a bottom face), wherein the exterior surfaces form a rectangular cuboid. Furthermore, both the front and rear surfaces of the square camera 100 are substantially square in shape. In one example embodiment, all camera surfaces may also have a substantially square profile, making the square camera 100 substantially cubic. In alternate embodiments, only two of the six faces are square and the other faces may be other shapes, such as elongated rectangles. The square camera 100 can have a small form factor (e.g. a height of 2 cm to 9 cm, a width of 2 cm to 9 cm, and a depth of 2 cm to 9 cm) and is made of a rigid material such as plastic, aluminum, steel, or fiberglass. Additional camera features, such as the features described below, may be affixed to an exterior of the square camera. In some embodiments, the square camera described herein includes features other than those described below. For example, instead of a single interface button, the square camera can include additional buttons or different interface features, such as a microphone opening to receive voice or other audio commands.

FIG. 1e illustrates a front view of the square camera, according to one embodiment. The front surface of the camera has a substantially square profile, such that all edges of the front surface are of roughly equal length. The front surface also includes a camera lens 102, which includes an aperture that allows light to pass through the lens 214 and onto an image sensor 206. The camera lens 102 can be any type of optical lens that facilitates capturing images or video, such as a wide-angle lens, an adjustable lens, a macro lens, and the like. While the camera lens 102 as shown in FIG. 1e is located in the center of the front surface, the camera lens 102 may be located anywhere on the front surface of the camera 100, or on any other surface. The camera lens 102 can protrude from the camera 100 or, as in the illustrated embodiment, can be flush with the front surface.

FIG. 1f illustrates a rear view of the square camera, according to one embodiment. The rear surface of the camera has a substantially square profile and has substantially similar dimensions to the front surface. While not shown in FIG. 1f, the rear surface of the square camera may further include a user interface, such as a screen, button, dial, viewfinder, or light, or a communicative interface, such as a USB or HDMI slot.

FIG. 1g illustrates a top view of the square camera, according to one embodiment. In this embodiment, the top surface has a substantially square profile with substantially similar dimensions to the front and rear surfaces; however, in other embodiments, the top surface may have a rectangular profile. The top surface features an interface button 104 and a display 106. The interface button 104 allows a user to interact with the camera. By pressing the button, a user may take a picture or record video, power on or off the camera, save a photo, adjust the camera focus, or perform any other action relevant to

4

recording or storing digital media. While this figure depicts the interface button 104 as a button, the interface button 104 may also be embodied as a knob, a switch, a dial, a touch-screen, a light (such as an LED), a speaker, or other forms of user interface. Furthermore, the camera may have more than one interface button 104. Even though the interface button 104 is located on the top surface of the substantially square camera, the interface button 104 may be located in any position on any surface.

The display (or screen) 106 allows the camera to output visual information to a user. In this figure, the display 106 is located on the top surface of the square camera, however, the display 106 may be located on any surface of the camera 100.

FIG. 2 is a block diagram illustrating one embodiment of electronic components of a square camera 100. The square camera 100 includes one or more processors 202 (generally, such as a digital signal processor or a microcontroller) that controls the operation and functionality of the camera. The processor 202 controls the operation of a lens and focus controller 204, an image sensor (or image sensor array) 206, a sensor controller 208, a system memory 210, an I/O controller hub 216, and a synchronization interface 220. In some embodiments, the camera 204 includes components other than those illustrated herein.

The image sensor 206 is configured to capture light incident upon the image sensor to produce image data based on control signals from the sensor controller 208. The lens and focus controller 214 is configured to control the operation and configuration of a camera lens. The system memory 210 is configured to store executable computer instructions that, when executed by the processor 202, perform the camera functionalities described herein. The camera 204 sends information (such as captured images and video) to and from the interface button 104 via the I/O controller hub. The processor 202 can store captured images and video in an external storage device 212, or can output captured images or video for display on an external display 224 via a graphics adapter 222. The synchronization interface 220 is configured to synchronize the camera 204 with other cameras or with other external devices, such as a remote control or a smart phone.

Square Camera Housing System Overview

FIG. 3a to FIG. 3d illustrate perspective views of an example narrow-frame square camera housing, according to one embodiment. As used herein, “square camera housing” refers to a camera housing with at least one substantially square cross-section. The square camera housing includes a housing body 300, a mounting mechanism 302, a latching mechanism 304, and a plurality of openings 306 configured to accommodate the interface button 104.

The housing body 300 is a structure that secures the square camera 100. The housing body 300 includes four walls or more (i.e., a top wall, a bottom wall, a left wall, and a right wall) that create a band around the square camera 100. Alternatively, the housing body 300 may be missing one or more of these walls (such as the top wall or a side wall) such that the housing body 300 is in the form of a U-shape instead of a band. In one example, the walls of the housing body 300 do not fully encompass various surfaces of the square camera 100 (such as the top surface, right surface, and left surface of the camera). In another example, the walls of the housing body 300 fully encompass one or more surfaces of the square camera 100. While the illustrated housing body 300 only includes four walls, other embodiments of the housing body feature additional walls. For example, a housing body 300 may include a front wall or a rear wall to further secure the camera in the housing body. In another example, the housing body may include additional walls that form a hexagonal or

5

octagonal housing to accommodate a similarly-shaped camera **100**. Additional features of the housing body **300** may include a housing lip, located along one or more interior edges of the body, to limit the depth to which the camera can be inserted into the housing body **300**. For example, a housing lip along the perimeter of the housing body's front face prevents the square camera **100** from being pushed out of the housing body **300** when the camera **100** is inserted from the rear.

The interior dimensions of the housing body **300** are similar to the exterior dimensions of the square camera frame, such that the square camera fits flush into the housing body. Furthermore, the housing body **300** in one example embodiment can have a small form factor (e.g. a height of 2 cm. to 10 cm., a width of 2 cm. to 10 cm., and a depth of 2 cm. to 10 cm.) and is lightweight (e.g. a weight of 25 to 150 grams).

The latching mechanism **304** can be configured in an open position such that the square camera can be inserted or removed from the housing body **300**, or can be configured to a closed position such that the square camera can be compressibly secured within the housing body. The housing body **300** can be made of a flexible material (e.g. plastic, polymer, metal, wood, or any other suitable material) that allows the walls to sufficiently deflect when the latching mechanism **304** is configured in an open position, allowing for the insertion or removal of the square camera from the housing body. Furthermore, the flexible material may exhibit material properties suitable for protecting the square camera **100** secured in the square camera housing from physical shock, abrasion, vibration, or environmental damage (e.g. water damage, dust, etc.). The latching mechanism **304** can be made of plastic, polymer, metal, wood, or any other suitable material.

It should be noted that while the description of the housing body **300** includes a description of separate walls, this does not necessarily imply that the housing body includes separate wall components welded, fastened, or otherwise connected. In one embodiment, the housing body **300** is fabricated as a single piece with no discernible boundaries between walls.

FIG. 3e to FIG. 3j illustrate views of the narrow-frame square camera housing, according to one embodiment. The figures illustrate features connected to the housing body **300**, including a plurality of protrusions **302**, a latching mechanism **304**, and a plurality of openings **306** to accommodate the camera interface button **104**.

A mounting mechanism allows the housing body **300** to be coupled to another object, such as bodywear, sporting equipment, or a vehicle. The mounting mechanism includes two protrusions **302** on the bottom surface of the housing body **300**. As seen in FIG. 3g and FIG. 3h, each protrusion **302** includes an aligning screw hole. The protrusions **302** are spaced such that the mounting mechanism can be coupled to a reciprocal mounting mechanism including additional protrusions that interlock with the protrusions **302**. The additional protrusions can also include screw holes that align with the screw holes of the protrusions **302** such that a screw (e.g., a turnable handscrew) may be inserted through the interlocking protrusions, coupling the housing body **300** to the reciprocal mounting mechanism. When the turnable handscrew is in an unlocked position, the housing body **300** can pivot rotationally relative to the reciprocal mounting device. When the turnable handscrew is in a locked position, the housing body **300** is fixed in position relative to the reciprocal mounting device.

The plurality of openings **306** are openings in the walls of the housing frame **300** that allow the square camera **100** to be oriented in multiple positions relative to the square camera housing such that the interface button **104** is accessible to a

6

user through one of the openings **306**. In FIG. 3g and FIG. 3h, the plurality of openings are each rectangular in shape and include a semi-elliptical cutout that accommodates the interface button **104**. However, other embodiments of the plurality of openings **306** may be any shape that accommodates one or more camera interfaces. The plurality of openings are located in the same relative position on each surface of the housing body **300** (e.g., on the top surface, the left surface, and the right surface) such that the camera body can be inserted and secured in the body in one of a plurality of orientations. For example, the plurality of openings **306** may allow the square camera **100** to be oriented in the frame vertically upright, rotated 90 degrees clockwise from vertical, or rotated 90 degrees counterclockwise from vertical. In other embodiments, the plurality of openings may be arranged such that the square camera **100** may be oriented in additional or alternative positions. Furthermore, a pliable waterproof or water-resistant material may be placed over the plurality of openings **306** to protect the camera from water or dust but not impede access to the interface button **104**.

In one embodiment, the square camera **100** is configured to identify an orientation of the camera within the housing body **300**. In such an embodiment, the square camera **100** can adjust the portion of the image sensor used to capture an image based on the identified orientation. For instance, if the square camera is inserted into the camera housing in an upright configuration, the square camera can capture an image from light incident upon a 16:9 ratio portion of the image sensor (and accordingly, can disregard light incident upon other portions of the image sensor, or can maintain image data from light incident upon such portions for use in subsequent image processing). Similarly, if the square camera is inserted into the camera housing in a 90 degrees clockwise from vertical orientation, the square camera can capture an image from light incident upon a 9:16 ratio portion of the image sensor, for instance for use in subsequent image processing to produce a 16:9 image. In these embodiments, the square camera **100** can include a square image sensor, and can be configured to adjust the portion of the image sensor used to capture an image.

In another example embodiment, the housing body **300** may not include a plurality of openings **306**. Instead, the housing body **300** may include one or more button interfaces that allow for user interaction with the square camera **100**. For example, the top wall, left wall, and right wall of the housing can each include one or more buttons or other compressible components configured to align with a camera interface when the camera is inserted into the camera housing in an associated orientation and to allow a user of the housing to interact with the camera interface using the compressible housing components.

FIG. 3k to FIG. 3t illustrate an embodiment of a wide-frame square camera housing. The wide-frame square camera housing has the same functionality as the narrow-frame square camera housing described in FIG. 3a to FIG. 3j. However, the wide-frame square camera housing includes walls that completely encompass the top, bottom, and side surfaces of the square camera **100**. Each wall of the wide-frame camera housing encompasses each corresponding side of the square camera **100**. Like the surfaces of the square camera **100**, the walls of the wide-frame housing body **300** are substantially square in shape. The interior dimensions of the housing body **300** are similar to the exterior dimensions of the square camera frame, such that the square camera fits flush within the housing body. Furthermore, the housing body **300** in one example embodiment has a small form factor (e.g., a

height of 2 cm. to 10 cm., a width of 2 cm. to 10 cm., and a depth of 2 cm. to 10 cm.) and is lightweight (e.g., a weight of 25 to 150 grams).

FIG. 4 illustrates a latching mechanism 304 for a square camera housing, according to one embodiment. The latching mechanism 304 includes a first hinge mechanism 402 coupled to a top wall of the housing body 300 and a second hinge mechanism 404 coupled to a side wall of the housing body. However, the latching mechanism 304 may be located on any surface of the housing body (for instance, the latching mechanism 304 can be located exclusively on the top wall, a side wall, or the bottom wall, or can be located at the intersection of a side wall and the bottom wall). The first 402 and the second 404 hinge mechanisms interlock such that when the latching mechanism 304 is configured in an open position, a gap 406 between the top wall and the side wall of the housing body 300 increases (or expands), increasing the inside perimeter of the housing body 300 and allowing for the insertion and removal of the square camera 100 from the housing body 300. When the first 402 and the second 404 hinge mechanisms are in a closed position, the gap 406 decreases (or shrinks), decreasing the inside perimeter of the housing body 300 and securing the square camera 100 within the housing body 300. The exteriors of both hinge mechanisms can be smooth and featureless, such that the latching mechanism does not catch on other objects or the surrounding environment. The latching mechanism 304 can be unlocked by lifting the first hinge mechanism 402.

In another example embodiment, the camera housing does not require a latching mechanism. In this embodiment, the camera housing includes a flexible/stretchable compressive band configured to compressibly secure a camera is within the housing. In such an embodiment, to insert a camera, the housing can be stretchably expanded to accommodate the insertion of the camera, and released to compressibly wrap around the exterior of the camera, securing the camera within the housing.

FIG. 5a illustrates the insertion of the square camera into the narrow-frame square camera housing, according to one embodiment. To insert the square camera 100 into the square camera housing, the latching mechanism 304 is unlocked and the square camera 100 is inserted into the housing body 300 in one of a plurality of orientations relative to the housing body 300. The square camera 100 may be inserted into the square camera housing through the front opening of the housing or the rear opening of the housing. A housing lip on one or more wall interiors, e.g., along an edge of each wall, may regulate the position of the square camera 100 within the housing. While the camera lens 102 is facing front in the exemplary orientations, the camera may be inserted such that the lens is facing the rear surface of the housing body 300. Furthermore, other embodiments of the square camera housing may accommodate the square camera 100 in additional or alternative orientations. Once the camera 100 is fully inserted into the housing body 300, the latching mechanism 304 is closed. The housing body 300 may be connected to a reciprocal mounting device either before or after the camera is inserted into the body.

FIG. 5b illustrates the camera inserted into the narrow-frame square camera housing in a first configuration, according to one embodiment. In the exemplary square camera housing embodied in FIG. 5b, the square camera 100 is inserted vertically upright into the square camera housing.

FIG. 5c illustrates the camera inserted into the narrow-frame square camera housing in a second configuration, according to one embodiment. The second configuration may include rotating the square camera 100 90 degrees clockwise

or 90 degrees counterclockwise around the front-rear axis. However, the square camera 100 may be inserted into the square housing body 300 in other configurations not disclosed in FIG. 5c.

FIG. 5b and FIG. 5c illustrate the square camera 100 secured in different orientations within the narrow-frame square camera mount. FIG. 5b shows the square camera 100 secured vertically upright in the square camera mount, while FIG. 5c shows the camera secured while rotated 90 degrees clockwise in the camera mount. Similarly, FIG. 5d-FIG. 5f illustrate the square camera 100 being inserted and secured in the wide-frame square camera mount.

Additional Configuration Considerations

Throughout this specification, some embodiments have used the expression “coupled” along with its derivatives. The term “coupled” as used herein is not necessarily limited to two or more elements being in direct physical or electrical contact. Rather, the term “coupled” may also encompass two or more elements that are not in direct contact with each other, but yet still co-operate or interact with each other, or are structured to provide a thermal conduction path between the elements.

Likewise, as used herein, the terms “includes,” “comprising,” “includes,” “including,” “has,” “having,” or any other variation thereof, are intended to cover a non-exclusive inclusion. For example, a process, method, article, or apparatus that includes a list of elements is not necessarily limited to only these elements but may also include other elements not expressly listed to such process, method, article, or apparatus.

In addition, use of the “a” or “an” are employed to describe elements and components of the embodiments herein. This is done merely for convenience and to give a general sense of the invention. This description should be read to include one or at least one and the singular also includes the plural unless it is obvious that it is meant otherwise.

Finally, as used herein, any reference to “one embodiment” or “an embodiment” means that a particular element, feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment. The appearances of the phrase “in one embodiment” in various places in the specification are not necessarily all referring to the same embodiment.

Upon reading this disclosure, those of skill in the art will appreciate still additional alternative structural and functional designs for a camera or camera housing as disclosed from the principles herein. Thus, while particular embodiments and applications have been illustrated and described, it is to be understood that the disclosed embodiments are not limited to the precise construction and components disclosed herein. Various modifications, changes, and variations, which will be apparent to those skilled in the art, may be made in the arrangement, operation, and details of the method and apparatus disclosed herein without departing from the spirit and scope defined in the appended claims.

What is claimed is:

1. A housing for a camera comprising:

a housing body, the housing body comprising a top wall, a left wall, a right wall, and a bottom wall of substantially equal length and configured to secure a camera in a plurality of orientations relative to the housing body, the housing body comprising a plurality of openings configured to accommodate a camera interface, each opening associated with one of the plurality of orientations and configured to allow a user of the camera to access the camera interface when the camera is inserted into the housing body in the associated orientation;

9

- a housing lip, along one or more interior edges of the housing body, to limit the depth to which the camera can be inserted into the housing body;
 - a latching mechanism configured to allow for the insertion or removal of the camera in an open position and to secure the camera within the housing in a closed position; and
 - a mounting mechanism on the bottom wall of the housing body configured to secure the housing to a reciprocal mounting mechanism.
2. The housing of claim 1, wherein the camera comprises: a substantially cubic camera body; a lens positioned on a front face of the camera body; and an interface on a face other than the front face that allows a user to interact with the camera.
 3. The housing of claim 1, wherein the latching mechanism is coupled to the top wall of the housing body and one of the right wall and the left wall of the housing body.
 4. The housing of claim 1, wherein the housing body is composed of a flexible material.
 5. The housing of claim 1, wherein the latching mechanism is composed of a plastic or metal.
 6. The housing of claim 1, wherein the latching mechanism includes multiple interlocking hinge mechanisms.
 7. The housing of claim 1, wherein the latching mechanism creates a gap between the top wall of the housing body and one of the left wall and the right wall of the housing body when the latching mechanism is in the open position.
 8. The housing of claim 1, wherein the camera is configured for insertion into one of a front or rear opening in the mounting body.
 9. A housing for securing a substantially cubic camera in a plurality of orientations, the housing comprising:
 - a housing body, wherein the housing body comprising a substantially cubic frame to secure the substantially cubic camera in the housing body in a plurality of orientations;
 - an opening, replicated on a plurality of faces belonging to the housing body, that accommodates an interface belonging to the substantially cubic camera;
 - a latching mechanism to secure the substantially cubic camera in the housing body;

10

- a mounting mechanism to facilitate a connection between the housing and another object;
 - a lip on the interior of the housing body, the lip to limit the depth the cubic camera can be inserted into the housing body.
10. A housing for a camera comprising:
 - a housing body, the housing body comprising a top wall, a left wall, a right wall, and a bottom wall of substantially equal length and configured to secure a camera with a substantially square cross section in a plurality of orientations relative to the housing body, wherein the housing body comprises an opening configured to accommodate a camera interface;
 - a latching mechanism configured to allow for the insertion or removal of the camera in an open position and to secure the camera within the housing in a closed position; and
 - a mounting mechanism on the bottom wall of the housing body configured to secure the housing to a reciprocal mounting mechanism.
 11. The housing of claim 10, wherein the camera comprises:
 - a substantially cubic camera body;
 - a lens positioned on a front face of the camera body; and
 - an interface that allows a user to interact with the camera.
 12. The housing of claim 10, wherein the latching mechanism is coupled to the top wall of the housing body and one of the right wall and the left wall of the housing body.
 13. The housing of claim 10, wherein the housing body is composed of a flexible material.
 14. The housing of claim 10, wherein the latching mechanism is composed of a plastic or metal.
 15. The housing of claim 10, wherein the latching mechanism includes multiple interlocking hinge mechanisms.
 16. The housing of claim 10, wherein the latching mechanism creates a gap between the top wall of the housing body and one of the left wall and the right wall of the housing body when the latching mechanism is in the open position.
 17. The housing of claim 10, wherein the camera is configured for insertion into a front or rear opening in the mounting body.

* * * * *